

## Product Specification

# SNZB-04

## Wireless Door/Window Sensor



### Basic Information

Product series	Smart Home Security
Type	Door/Window Sensor
Battery model	CR2032 (3V)
Quiescent current	<2uA
Emission current	Mean value: <15mA 30mA max.
Installation gap	<10mm
MCU	CC2530
Certification	CE/FCC/ROHS

### Appearance

Color	White
Dimension	Transmitter: 47x27x13.5mm    Magnet: 35x15.6x13mm
Weight	20g
Casing material	PC V0

### Features

Functions	Low-energy, monitor the opening and closing status of doors or windows through separating the transmitter from the magnet. Trigger other connected devices on or off via smart scene.
Pairing time	30s
Matched gateways	SONOFF ZBBridge and gateways supporting ZigBee 3.0 wireless protocol. Detailed information is in accordance with the final product.

### Wireless standard

ZigBee	IEEE 802.15.4
Antenna	PCB board with antenna
Security mode	WPA/WPA2
Encryption type	AES-128
Signal strength	<20 dBm

### Working Environment

Applicable place	Indoor
Working temperature	-10°C ~ 40°C
Working humidity	5%-95% RH, non-condensing
Working height	Less than 2000m

### Installation

Installation method	3M adhesive to stick
---------------------	----------------------