



Reyee RG-ES100

Unmanaged Switches Datasheet

Ruijie Networks Co.,Ltd

Floor 11,East Wing, Zhongyipengao Plaza,
No.29 Fuxing Road, HaidianDistrict, Beijing China

Website : <https://www.ruijienetworks.com>



RG-ES116G



RG-ES124GD

Model	RG-ES116G	RG-ES124GD
Hardware specifications		
Ports	16*10/100/1000 Mbps ports	24*10/100/1000 Mbps ports
Operating mode	Half-duplex, full-duplex, auto-negotiation mode	
	Support auto MDI/MDIX	
Switching capacity	32Gbps	48Gbps
Package forwarding rate	23.81Mpps	35.71Mpps
MAC address	8K	8K
Power supply	100-240V AC	100-240V AC
Port Mode	"Flow Control On", "Flow Control Off", "Port Isolation", "Extend Data Transmission-10Mbps" from left to right	
Power consumption	11W	16W
PoE	Not support	
Fan	N/A	N/A
Dimensions (W x D x H)	280 x 126 x 44mm	280 x 126 x 44mm
Operating temperature	0°C to 45°C	
Storage temperature	-40°C to 70°C	
Operating humidity	10% to 90% RH	
Storage humidity	5% to 95% RH	

Ordering Information

Model	Description
RG-ES116G	16 10/100/1000M copper ports; unmanaged switch; desktop type; rack-mount supported.
RG-ES124GD	24 10/100/1000M copper ports; unmanaged switch; desktop type; rack-mount supported.